



Weyn-Lauwers N.V.

INDUSTRIEPARK-NOORD 12
B - 9100 SINT-NIKLAAS

TEL. 0032 (0)3 776.34.13
FAX. 0032 (0)3 778.09.52

weynlauwers@weynlauwers.be
www.weynlauwers.be

GATE VALVE
SOFT SEALED
GGG 50 - PN16
fig 315

FEATURES

- full bore with minimal pressure drop
- maintenance free
- can be installed in any position
- hydraulic tested according to BS 6755
- working pressure : 16 bar
- threaded BSP MF

MATERIALS

- body : ductile iron GGG50
- cover : ductile iron GGG50
- stem : stainless steel AISI 304
- wedge : ductile iron GGG50 + NBR
: on request GGG50 + EPDM
- stem sealing : NBR (on request EPDM)
- coating : epoxy 250 micron
- stem nut : brass



DIMENSIONS

Size		ref.	H mm	H1 mm	L mm	L1 mm	weight kg
ND	ND1						
3/4"	5/4"		165	238	47	94	2,80
1"	5/4"		165	238	47	94	2,70
5/4"	5/4"		165	238	47	94	2,70
5/4"	2"		210	304	60	118	5,00
6/4"	2"		210	304	60	118	5,00
2"	2"		210	304	60	118	4,80

