



Weyn-Lauwers N.V.

INDUSTRIEPARK-NOORD 12
B - 9100 SINT-NIKLAAS

TEL. 0032 (0)3 776.34.13
FAX. 0032 (0)3 778.09.52

weynlauwers@weynlauwers.be
www.weynlauwers.be

GATE VALVE SOFT SEALED - GGG 50 INSIDE SCREW F5 - PN16 fig 335

FEATURES

- full bore with minimal pressure drop
- maintenance free
- can be installed in any position
- hydraulic tested according to BS 6755
- working pressure : 16 bar
- flanges according DIN 2501
- according DIN 3202 F5

MATERIALS

- body : ductile iron GGG50
- cover : ductile iron GGG50
- stem : stainless steel AISI 304
- wedge : ductile iron GGG50 + NBR
: on request GGG50 + EPDM
- stem sealing : NBR (on request EPDM)
- coating : epoxy 250 micron
- stem nut : brass



DIMENSIONS

Size ND	ref.	H mm	H1 mm	L mm	weight kg
40	206720	415	340	240	13
50	206721	428	345	250	15
65	206722	473	380	270	23
80	206723	500	400	280	26
100	206724	540	430	300	34
125	206725	645	520	325	53
150	206726	683	540	350	60
200	206727	815	645	400	95
250	206728	943	740	450	154
300	206729	1070	840	500	241
350		1160	900	550	355
400		1310	1020	600	475

