



Weyn-Lauwers N.V.

INDUSTRIEPARK-NOORD 12
B - 9100 SINT-NIKLAAS

TEL. 0032 (0)3 776.34.13
FAX. 0032 (0)3 778.09.52

weynlauwers@weynlauwers.be
www.weynlauwers.be

SCHUIFAFSLUITER
staal GS-C25 F5

fig 371
PN 25

KEIL-RUNDSCHIEBER AUS STAHL MIT BOCKAUFSATZ
GATE VALVES OF CAST STEEL + OUTSIDE SCREW & YOKE

GS-C25

PN 25

		1	BODY	GS-C25	12	GLAND	A182 F6
		2	SEAT RING	A 105	13	GLAND FLANGE	GS-C25
		3	WEDGE	GS-C25	14	GLAND NUT	A 914 2H
		4	STEM	X20Cr13	15	WASHER	A 307 B
		5	GASKET	S.S. + GRAPHITE SPIRALE WOUND	16	BONNET	GS-C25
		6	STUD	A 193 B7	17	GREASE NIPPLE	CARBON STEEL
		7	BONNET NUT	A 194 2H	18	STEM NUT	A 439 D2
		8	BACKSEAT BUSHING	A 182 F6	19	RETAINING NUT	CARBON STEEL
		9	PACKING	GRAFOIL	20	HANDWHEEL	DUCTILE IRON OR STEEL
		10	PIN	CARBON STEEL	21	HANDWHEEL NUT	A 307 B
		11	EYEBOLT	A 307 B	22	NAMEPLATE	AL

**FLANSCH-
MÄßE**
FLANGE
DIMENSIONS:
DIN 2501

BAULÄNGE
**FACE-TO-
FACE**
DIMENSIONS:
EN 558-1 (15)
TESTS:
DIN 3352-T1

DN	D ₂	D ₁	D	F	B	Z-Ø _D	L	H _{MAX}	D ₀	KG
15	45	65	95	2	16	4-Ø14	130	195	120	
20	58	75	105	2	18	4-Ø14	150	205	140	
25	68	85	115	2	18	4-Ø14	160	240	160	
32	78	100	140	2	18	4-Ø18	180	240	180	
40	88	110	150	3	18	4-Ø18	240	350	203	12
50	102	125	165	3	20	4-Ø18	250	390	230	13
65	122	145	185	3	22	8-Ø18	270	420	230	26
80	138	160	200	3	24	8-Ø18	280	465	254	30
100	162	190	235	3	24	8-Ø18	300	560	254	40
125	188	220	270	3	26	8-Ø22	325	670	305	60
150	218	250	300	3	28	8-Ø26	350	765	355	71
200	278	310	360	3	30	12-Ø26	400	970	406	120
250	335	370	425	3	32	12-Ø30	450	1165	455	200
300	395	430	485	4	34	16-Ø30	500	1370	508	300
350	450	490	555	4	38	16-Ø33	550	1520	559	560
400	505	550	620	4	40	16-Ø36	600	1720	610	680
500	615	660	730	4	44	20-Ø36	700	2120	710	1050
600	720	770	845	5	46	20-Ø39	800	2515	762	1500

ABBILDUNGEN UND MATERIALANGABEN SIND UNVERBINDLICH
DESIGN AND MATERIALS CAN BE CHANGED WITHOUT NOTICE
IRRTUM VORBEHALTEN - ERRORS AND OMISSIONS EXCEPTED