



Weyn-Lauwers N.V.

Industriepark-Noord 12
B - 9100 SINT-NIKLAAS

Tel. : 00 32 (0)3 776.34.13
Fax : 00 32 (0)3 778.09.52
weynlauwers@weynlauwers.be
www.weynlauwers.be

SAFETY VALVES VACUUM BREAKER INDEX

INDEX

Type of valve	Connections	Rating	Material	Pag.	
1. BRONZE VALVE					
1.1 Model 800	Threaded	BSP and NPT	PN-25	Bronze	3
2. THREADED VALVE					
2.1 Model 1216	Threaded	BSP and NPT	PN-40	Stainless steel	4
2.2 Model 1216 HP	Threaded	BSP and NPT	PN-100-400	Stainless steel	5
3. FLANGES					
3.1 Model 1216B	ANSI x ANSI or BSP or NPT	150# RF 300# RF	Stainless steel Stainless steel	6	
	EN x EN or BSP or NPT	PN 16 PN 40	Stainless steel Stainless steel		
3.2 Model 1400	Flanges	EN	PN-16 PN-25 PN-40 PN-63 PN-100		Nodular/ carbon steel/ stainless steel Nodular/ carbon steel/ stainless steel Carbon steel and stainless steel Carbon steel and stainless steel Carbon steel and stainless steel
3.3 Model 1415	Flanges	ANSI B 16.5	150# RF 300# RF 600# RF 900# RF 1500# RF	Carbon steel and stainless steel Carbon steel and stainless steel Carbon steel and stainless steel Carbon steel and stainless steel Carbon steel and stainless steel	9
5. CLAMP VALVES					
5.1 Model 1216C	CLAMP	ISO 2852	PN-10	Stainless steel	12
6. VACUUM RELIEF VALVES					
6.1 Model 1000	Flanges/Threaded		PN-10	Al / Carbon steel/ Stainless steel	13
6.1 Model 1100	Flanges/Threaded		PN-10	Al / Carbon steel/ Stainless steel	14
7. ACCESORIES					
7.1 Accesories	EN/ANSI		PN-10/400	Stainless steel / Al/ Nickel/ Monel Inconel/ Hastelloy C276	15