



**Weyn-Lauwers** N.V.

Industriepark-Noord 12  
B - 9100 SINT-NIKLAAS

Tel. : 00 32 (0)3 776.34.13  
Fax : 00 32 (0)3 778.09.52  
weynlauwers@weynlauwers.be  
www.weynlauwers.be

## SAFETY VALVES Accessories

### Lifting device



Manual lifting device.  
Steam service must have  
lifting device.

### Test gag



To test pressure of the installation.  
After testing test gag must be  
removed.  
Test gag is possible for safety  
transport of the valve.

### Lift indicator



Proximity switch and valve position  
indicator.  
Inductive prox 3-wire switching type  
Supply voltage 20 to 264 VAC,  
50/60 Hz.  
Enclosure ratings IEC 144 IP67  
Option Eex / ATEX

### Packing lever



Manual lifting device.  
This system to ensure that the fluid  
do not escape to the atmosphere.

### Nozzle ring/Blowdown ring



To help the control flow capacity.  
Adjustable blowdown

### Specials spring



Carbon steel	120° C
Chrome Vanadium	219° C
S.S. AISI.302	260° C
Inconel X-750	500° C

### Bellows



To protect:  
Constant back pressure  
Variable back pressure  
Material: S.S. AISI-316TI  
Max. Back pressure 40%

### Trim in hastelloy



Nozzle and disc: Hastelloy C 276  
( Nickel-molybdenum-tungsten alloy)  
Excellent general corrosion resistance  
Rest of valve: S.S. AISI-316L  
Bursting disc

### Stellite in the seat



In PN-63, PN-100  
600#, 900# and 1500#

### Heating Jacket



Areas of application are system  
to be protected from media  
which are viscous and have  
tendency to crystallise.  
Material: S.S. AISI-316L