



**Industriepark-Noord 12  
B - 9100 SINT-NIKLAAS**

[www.weynlauwers.be](http://www.weynlauwers.be)

**type G**

- voor watervoorziening tot max. 16 bar
- temp : max.60°C
- voor alle soorten buizen

| nr | omschrijving     | materiaal                                     |
|----|------------------|-----------------------------------------------|
| 1  | huis             | nodulair gietijzer GGG50<br>met epoxy coating |
| 3  | dichting         | EPDM                                          |
| 4  | bouten en moeren | staal                                         |



|             |     |     |     |     |     |     |     |     |     |     |     |     |     |
|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| DN          | 50  | 65  | 80  | 100 | 125 | 150 | 175 | 200 | 200 | 250 | 250 | 300 | 300 |
| min. diam.  | 60  | 70  | 88  | 107 | 133 | 159 | 165 | 194 | 216 | 244 | 266 | 315 | 345 |
| max. diam.  | 80  | 90  | 113 | 132 | 159 | 184 | 195 | 226 | 246 | 276 | 297 | 345 | 375 |
| max. bar    | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  | 16  |
| length (mm) | 145 | 145 | 150 | 125 | 140 | 175 | 183 | 158 | 183 | 158 | 158 | 158 | 200 |

**type A**

- aanboorzadel voor watervoorziening tot max. 10 bar
- temp : max.60°C
- voor alle soorten buizen

| nr | omschrijving     | materiaal |
|----|------------------|-----------|
| 1  | huis             | gietijzer |
| 2  | beugel           | RVS 304   |
| 3  | dichting         | NBR       |
| 4  | bouten en moeren | RVS 304   |

[illegible]